Lucent Technologies
Bell Labs Innovations



APX™/MAX TNT®

TAOS 10.0.3 Release Note

For software version 10.0.3
April 9, 2003

Copyright © 2003 Lucent Technologies Inc. All rights reserved.

This material is protected by the copyright laws of the United States and other countries. It may not be reproduced, distributed, or altered in any fashion by any entity (either internal or external to Lucent Technologies), except in accordance with applicable agreements, contracts, or licensing, without the express written consent of Lucent Technologies. For permission to reproduce or distribute, please email your request to techcomm@lucent.com.

Notice

Every effort was made to ensure that the information in this document was complete and accurate at the time of printing, but information is subject to change.

European Community (EC) RTTE compliance

CE Hereby, Lucent Technologies, declares that the equipment documented in this publication is in compliance with the essential requirements and other relevant provisions of the Radio and Telecommunications Technical Equipment (RTTE) Directive 1999/5/EC.

To view the official *Declaration of Conformity* certificate for this equipment, according to EN 45014, access the Lucent INS online documentation library at http://www.lucentdocs.com/ins.

Safety, compliance, and warranty information

Before handling any Lucent Access Networks hardware product, read the *Edge Access and Broadband Access Safety and Compliance Guide* included in your product package. See that guide also to determine how products comply with the electromagnetic interference (EMI) and network compatibility requirements of your country. See the warranty card included in your product package for the limited warranty that Lucent Technologies provides for its products.

Security statement

In rare instances, unauthorized individuals make connections to the telecommunications network through the use of access features.

Trademarks

Lucent, the Lucent logo, and all Lucent brand and product names are trademarks or registered trademarks of Lucent Technologies Inc. Other brand and product names are trademarks of their respective holders.

Ordering information

You can order the most up-to-date product information and computer-based training online at http://www.lucentdocs.com/bookstore.

Feedback

Lucent Technologies appreciates customer comments about this manual. Please send them to techcomm@lucent.com.

Lucent Technologies

Customer Service

Product and service information, and software upgrades, are available 24 hours a day. Technical assistance options accommodate varying levels of urgency.

Finding information and software

To obtain software upgrades, release notes, and addenda for this product, log in to Lucent OnLine Customer Support at `http://www.lucent.com/support`.

Lucent OnLine Customer Support also provides technical information, product information, and descriptions of available services. The center is open 24 hours a day, seven days a week. Log in and select a service.

Obtaining technical assistance

Lucent OnLine Customer Support at `http://www.lucent.com/support` provides easy access to technical support. You can obtain technical assistance through email or the Internet, or by telephone. If you need assistance, make sure that you have the following information available:

- Active contract number, product name, model, and serial number
- Software version
- Software and hardware options
- If supplied by your carrier, service profile identifiers (SPIDs) associated with your line
- Your local telephone company's switch type and operating mode, such as AT&T 5ESS Custom or Northern Telecom National ISDN-1
- Whether you are routing or bridging with your Lucent product
- Type of computer you are using
- Description of the problem

Obtaining assistance through email or the Internet

If your services agreement allows, you can communicate directly with a technical engineer through Email Technical Support or a Live Chat. Select one of these sites when you log in to `http://www.lucent.com/support`.

Calling the technical assistance center (TAC)

If you cannot find an answer through the tools and information of Lucent OnLine Customer Support or if you have a very urgent need, contact TAC. Access Lucent OnLine Customer Support at `http://www.lucent.com/support` and click `Contact Us` for a list of telephone numbers inside and outside the United States.

Alternatively, call 1-866-LUCENT8 (1-866-582-3688) from any location in North America for a menu of Lucent services. Or call +1 510-769-6001 for an operator. If you do not have an active services agreement or contract, you will be charged for time and materials.

Contents

Customer Service iii

Section 1 Upgrading and Downgrading 1

APX 8000 upgrade and downgrade procedures 1
- Requirements and recommendations 1
- APX 8000 upgrade instructions 3
- APX 8000 downgrade instructions 5

APX 1000 and MAX TNT upgrade and downgrade procedures 6
- Requirements and recommendations 6
- APX 1000 and MAX TNT upgrade instructions 10
- APX 1000 and MAX TNT downgrade instructions 11

Section 2 Enhancements and Corrections in TAOS 10.0.3 13

TAOS 10.0.3 enhancements 13
- Firmware versions for digital modem cards 13
- Firmware versions for MultiDSP cards 13

Problems corrected in TAOS 10.0.3 14

Section 3 Enhancements and Corrections in TAOS 10.0.2 19

TAOS 10.0.2 enhancements 19
- Improved POST diagnostics for slot cards 19
- Firmware versions for digital modem cards 19
- Firmware versions for MultiDSP cards 19
- Enhanced VoIP signaling 20
- IP-within-IP security enhanced 21
- Log profile enhanced 22

Problems corrected in TAOS 10.0.2 23

Section 4 Enhancements and Corrections in TAOS 10.0.1 27

TAOS 10.0.1 enhancements 27
- Firmware versions for digital modem cards 27
- Firmware versions for MultiDSP cards 27
- Support for the 288-port and 240-port MultiDSP card 27
- Support for the APX Ethernet slot card 28

Problems corrected in TAOS 10.0.1 28

Section 5 Notices, Known Issues, and Caveats in TAOS 10.0.3 29

Notices in TAOS 10.0.3 29
- Notice of TAOS license and upgrade changes 29
- Notice of discontinued support for multishelf functionality 30
- Notice of parameter name changes in the external-auth profile 30
- Notice of change in supported values for the signaling mode 31
- Notice about MultiDSP slot cards 31
- Notice of TAOS interoperability with SS7 signaling software 31
- Notice of discontinuance of configurable RADIUS port and ID space 32
- Notice of discontinuance of software support 32
- Notice of deprecated management features 32
- Notice of discontinuance of support for AppleTalk and ARA routing 33
- Notice concerning call signaling support on T1/E1 slot cards 33

Known issues in TAOS 10.0.3 34
- Known issue using multiple OC3-ATM2 slot cards 34
- Known issue sorting call routing types 34
- Known issue receiving warning messages when saving profiles 34
- Known issue handling full BGP Internet routing table 34
- Known issue with 96-port MultiDSP slot card 34

Caveats in TAOS 10.0.3 35

Upgrading and Downgrading 1

APX 8000 upgrade and downgrade procedures 1-1

APX 1000 and MAX TNT upgrade and downgrade procedures 1-6

APX 8000 upgrade and downgrade procedures

This section shows how to upgrade and downgrade the TAOS software of an APX 8000 unit.

Requirements and recommendations

These recommendations for upgrading TAOS units help ensure a smooth upgrade. If you must downgrade from this release to an earlier TAOS release, please see "APX 8000 downgrade instructions" on page 1-5.

Obtaining the TAOS 10.0.2 software

The TAOS 10.0.2 software for the APX 8000 consists of the following files:

Filename	Descriptions
`apxsrb.bin`	The boot loader. Both T1 and E1 loads use the same boot loader software. Install the appropriate boot loader for your release when upgrading or downgrading.
`apxrel.tar` and `apxrel2.tar`	Tar files (T1 load) that contain images for the shelf controller and all T1-compatible slot cards.
`apxrele.tar` and `apxrele2.tar`	Tar files (E1 load) that contain images for the shelf controller and all E1-compatible slot cards.

If you need further assistance on how to obtain the TAOS 10.0.2 software, see "Customer Service" on page iii.

To identify the software that you need based on the slot cards that have been physically installed in your chassis, refer to the following table. This table lists the contents of the tar files that contain the most commonly used slot-card images.

Minimally, you must load the first tar file (`apxrel.tar` or `apxrele.tar`). If your APX 8000 chassis contains additional slot cards (for example, a SWAN slot card), then you must also load the second tar file (`apxrel2.tar` or `apxrele2.tar`).

The contents of the APX 8000 TAOS 10.0.3 tar files are listed in Table 1-1.

Table 1-1. TAOS 10.0.2 APXC 8000 tar files

Filename	Description	Slot-card images
apxrel.tar	Shelf controller	apxsr
	Ethernet	tntenet2 tntenet3 tntenet3nd
	HDLC	tnthdlc2 tnthdlc2ec
	T1-specific images	tnt8t1 tntt3 tntut1 tntpctfit
	APX 8000 MultiDSP modem images	tntmadd tntmadd3
apxrel2.tar	STM-0	tntstm0
	UDS3	tntuds3
	DS3-ATM, DS3-ATM-2	tntds3atm tntds3atm2
	OC3-ATM, OC3-ATM-2	tntoc3atm tntoc3atm2
	SWAN	tntswan tntswan2
apxrele.tar	Shelf controller	apxsre
	Ethernet	tntenet2 tntenet3 tntenet3nd apxenet
	HDLC	tnthdlc2 tnthdlc2ec
	E1-specific images	tnt8e1 tntue1 tntpctfie
	APX 8000 MultiDSP modem images	tntmadd tntmadd3
apxrele2.tar	E3-ATM	tnte3atm
	OC3-ATM, OC3-ATM-2	tntoc3atm tntoc3atm2
	SWAN	tntswan tntswan2

Local access to the unit recommended

Whenever you install system software, Lucent recommends that you access the unit through the shelf controller serial or LAN port rather than a slot card port.

Saving the system configuration

As a general practice, always save the system configuration before upgrading or downgrading system software. If you use TFTP to save the system configuration, the target file must exist on the TFTP server and you must have permission to write it. For example, the following commands executed on a TFTP server create a target file and set its permissions:

```
$ touch /tftpboot/config/testcfg.1
```

```
$ chmod a=rw /tftpboot/config/testcfg.1
```

Before you save the system configuration, you must enable the `allow-password` permission in the user profile to save the configured passwords. If you do not have `allow-password` permission enabled, you will be prompted to confirm that you wish to save the configuration without passwords. If you do so and then restore the saved configuration, all passwords in the configuration are wiped out. The following commands executed on the APX 8000 unit save the system's configuration to the target file on the TFTP server and then restore the saved configuration:

```
admin> save network 10.10.10.10 config/testcfg.1
```

```
admin> load config network 10.10.10.10 config/testcfg.1
```

For additional information about the save command and its options, see the *APX 8000/MAX TNT Reference*.

Upgrade synchronization on systems with dual controllers

If you are logged into the primary controller and use one of the following commands, the effect is system wide:

Command	Description
`load`	Load a new software version.
`nvram`	Clear NVRAM.
`reset`	Reset the system, dropping all calls.

By default, when logged into the primary controller, these commands affect both controllers. However, you can specify command options to restrict the operation to a specific controller.



Note If you are logged into the secondary controller and use the `nvram` or `reset` command, the operation affects only the secondary controller. The secondary controller cannot reset or clear the memory of the primary controller.

APX 8000 upgrade instructions

These instructions show how to upgrade to TAOS 10.0.3 from an earlier TAOS version. The instructions apply to both single-controller and dual-controller APX 8000 units.



Note Under certain conditions, the `load tar` command might recognize no slot cards and load only the shelf controller image during the upgrade procedure. If this

occurs, reset the system and load the tar files again. The second load tar command loads the appropriate slot-card images for the system.

Before you begin upgrading

Before upgrading the APX 8000 unit, follow these preliminary steps:

1. **Log into the hard IP address of the primary controller and save its configuration to a TFTP server.**

   This step is optional but strongly recommended. For details, see "Saving the system configuration" on page 1-9.

2. **Verify that the `load-select` profile is configured to either automatically load only required binaries or to load only selected binaries.**

Upgrading an APX 8000 unit



Caution The following steps are order sensitive. To help ensure a smooth upgrade first perform the preliminary upgrade steps described in the preceding section, and then perform the steps in the order in which they are shown.

To upgrade an APX 8000 unit, proceed as follows.

1. **Log into the hard IP address of the primary shelf controller. Do not use the soft IP address. Use the `dir ip-interface` command to locate the primary controller's profile if needed to obtain the IP address.**
2. **Load the boot loader. For example:**

   ```
   admin> load boot-sr network 10.10.10.10 apxsrb.binaries/apxsrb.bin
   ```



Note If you only need the first required tar file, continue with step 3. If you need both tar files, go to step 5.

3. **Load the tar file. For example:**

   ```
   admin> load tar network 10.10.10.10 apxrel.tar
   ```



Note Use the `ls` and `version` commands to verify that the slot cards on your system have the equivalent file on the flash card. If a slot-card image is missing, continue with step 4; otherwise continue with step 6.

4. **Reset the system.**

   For example:

   ```
   admin> reset
   ```

   The `reset` command on the primary controller resets both controllers, dropping all calls. The system should come up with the existing configuration intact. If so, go to step 6. Otherwise, if unexpected circumstances result with an incomplete configuration (such as, physically installed cards still not being reconfigured), continue with step 5.

5. **Load the tar files as follows:**

   ```
   admin> load tar network 10.10.10.10 apxrel.tar apxrel2.tar
   ```

6. **Restore the system configuration (optional).**

   For example:

   ```
   admin> load config network 10.10.10.10 /tftpboot/config/apxconfig
   ```

7 **Reset the system as follows:**

```
admin> reset
```

8 **In the `ip-global` profile, set the `system-IP-address` parameter to 0.0.0.0.**

This step allows you to set the `ip-address` parameter in the primary `ip-interface` profile for the primary IP interface without interference from a global `system-ip-address` value.

9 **In the `IP-INTERFACE/{ { shelf-1 slot-primary 0 } 0 }` profile, set the `ip-address` parameter to *x.x.x.x*.**

Configure the primary IP interface. This IP address is always connected to the shelf controller that is functioning as primary.

10 **Set the `system-IP-address` parameter in the `ip-global` profile to the same IP address, *x.x.x.x*.**

The `system-ip-address` must always match the IP address of the unit's primary slot IP interface address.

11 **In `IP-INTERFACE/{ { any-shelf any-slot 0 } 0 }` set the `ip-address` parameter to a value that is not *x.x.x.x* if a soft IP address is desired.**

Note If your unit is configured with DNIS and CLID passwords, after upgrading from TAOS 9.0.x or 10.0.0 to TAOS 10.0.x, the unit no longer recognizes the `dnis-password` and `clid-password` values that were set in prior releases and dial-in users may experience a busy tone. See "Notice of parameter name changes in the external-auth profile" on page 5-30 for additional information.

APX 8000 downgrade instructions

Note If you must downgrade, you must have serial access to the unit. See the APX 8000 TAOS 9.0 or 9.1 release note at `http://www.lucent.com/support`.

Because releases are not necessarily backward compatible, Lucent recommends that you always restore a backup configuration made under the previous version. To restore the previous software version (TAOS 9.0.x, 9.1.x, or 10.0.0), proceed as follows:

1 **Load the previous version of the boot loader.**

For example:

```
admin> load boot-sr network 10.10.10.10 apxsrb.bin
```

2 **Format the flash cards of both the primary and the secondary controller:**

```
admin> format flash-card-1
```

To restore it to a previous software version prior to version 9.0.x, continue with step 3. Otherwise, continue with step 4.

3 **Load the previous version of the tar file. For example, to load via TFTP from a local host:**

```
admin> load tar network 10.10.10.10 apxrel.tar
```

Note Skip step 4.

4 **Load the previous version of the files.**

```
admin> load tar network 10.10.10.10 apxrel.tar apxrel2.tar
```

5 **Clear all profiles by entering the `nvram` command, for example:**

```
admin> nvram
```

6 **Log into the primary shelf controller via the serial connection. Open the `ip-interface` profile for the shelf controller and set the address.**

For example:

```
admin> read ip-interface { { 1 right-controller 1 } 0}
IP-INTERFACE/{ { shelf-1 right-controller 1 } 0 } read

admin> set ip-address = 10.10.10.2/24

admin> write
IP-INTERFACE/{ { shelf-1 right-controller 1 } 0 } written
```

7 **Load a backup configuration made under the restored software version or one of its predecessors.**

For example:

```
admin> load config network 10.10.10.10 config/backup-config
```

8 **Reset the system. This step is required.**

For example:

```
admin> reset
```

APX 1000 and MAX TNT upgrade and downgrade procedures

This section shows how to upgrade and downgrade the TAOS software of an APX 1000 or MAX TNT unit.

Requirements and recommendations

These recommendations for upgrading APX 1000 and MAX TNT units help ensure a smooth upgrade. If you must downgrade from this release to a previous one, please see "APX 1000 and MAX TNT downgrade instructions" on page 1-11.

Obtaining the TAOS 10.0.3 software for the APX 1000

The TAOS 10.0.3 software for the APX 1000 consists of the following files:

Filename	Descriptions
`apx1ksrb.bin`	The boot loader. Both T1 and E1 loads use the same boot loader software. Install the appropriate boot loader for your software release when upgrading or downgrading.
`apx1krel.tar`	Tar files (T1 load) that contain images for the shelf controller and all T1-compatible slot cards.
`apx1krele.tar`	Tar files (E1 load) that contain images for the shelf controller and all E1-compatible slot cards.

You can obtain the files you need from `www.lucent.com/support`. If you need technical assistance, see "Customer Service" on page iii.

To identify the software that you need based on the slot cards that have been physically installed in your chassis, refer to Table 1-2. This table lists the contents of the tar files that contain the most commonly used slot-card images.

You must load the tar file `apx1krel.tar` or `apx1krele.tar`. The contents of the APX 1000 TAOS 10.0.3 tar files are listed in Table 1-2.

Table 1-2. TAOS 10.0.2 APX 1000 tar files

Filename	Description	Slot-card images
`apx1krel.tar`	Shelf controller	`apx1ksr`
	Ethernet	`tntenet3nd`
	Hybrid Access	`tnthdlc2ec`
	T1 and T3	`apx1k24t1 tnt8t1 tntt3`
	MultiDSP	`tntmadd tntmadd3`
	DS3-ATM	`tntds3atm2`
	OC3-ATM	`tntoc3atm2`
	Serial WAN	`tntswan2`
`apx1krele.tar`	Shelf controller	`apx1ksre`
	Ethernet	`tntenet3nd`
	Hybrid Access	`tnthdlc2ec`
	E1	`apx1k24e1 tnt8e1`
	MultiDSP	`tntmadd tntmadd3`
	OC3-ATM	`ttntoc3atm2`
	Serial WAN	`tntswan2`

Obtaining the TAOS 10.0.3 software for the MAX TNT

The TAOS 10.0.3 software for the MAX TNT consists of the following files:

Filename	Descriptions
`tntsrb.bin`	The boot loader. Both T1 and E1 loads use the same boot loader software. Install the appropriate boot loader for your software release when upgrading or downgrading.
`tntrel.tar` and `tntrel2.tar`	Tar files (T1 load) that contain images for the shelf controller and all T1-compatible slot cards.
`tntrele.tar` and `tntrele2.tar`	Tar files (E1 load) that contain images for the shelf controller and all E1-compatible slot cards.

You can obtain the files you need from `www.lucent.com/support`. If you need technical assistance, see "Customer Service" on page iii.

To identify the software that you need based on the slot cards that have been physically installed in your chassis, refer to Table 1-3. This table lists the contents of the tar files that contain the most commonly used slot-card images.

Minimally, you must load the first tar file (`tntrel.tar` or `tntrele.tar`). If your MAX TNT chassis contains additional slot cards (for example, an E3-ATM slot card), then you must also load the second tar file (`tnt rel2.tar` or `tntrele2.tar`).

The contents of the MAX TNT TAOS 10.0.3 tar files are listed in Table 1-3:

Table 1-3. TAOS 10.0.2 MAX TNT tar files (page 1 of 2)

Filename	Description	Slot-card images
`tntrel.tar`	Shelf controller	`tntsr`
	Ethernet	`tntenet2 tntenet3 tntenet3nd`
	HDLC	`tnthdlc2 tnthdlc2ec`
	T1-specific images	`tnt8t1 tntt3 tntut1 tntpctfit`
	MAX TNT MultiDSP modem images	`tntcsmx tntcsm3v tntmadd`
	SWAN	`tntswan`
`tntrel2.tar`	STM-0	`tntstm0`
	UDS3	`tntuds3`
	DS3-ATM, DS3-ATM-2	`tntds3atm tntds3atm2`
	OC3-ATM, OC3-ATM-2	`tntoc3atm tntoc3atm2`
	SWAN	`tntswan tntswan2`
`tntrele.tar`	Shelf controller	`tntsre`
	Ethernet	`tntenet2 tntenet3 tntenet3nd apxenet`
	HDLC	`tnthdlc2 tnthdlc2ec`
	SWAN	`tntswan`
	E1-specific images	`tnt8e1 tntue1 tntpctfie`
	MAX TNT MultiDSP modem images	`tntcsmx tntcsm3v tntmadd`

Table 1-3. TAOS 10.0.2 MAX TNT tar files (page 2 of 2)

Filename	Description	Slot-card images
tntrele2.tar	E3-ATM	tnte3atm
	OC3-ATM, OC3-ATM-2	tntoc3atm tntoc3atm2
	SWAN	tntswan tntswan2

Local access to the unit recommended

Whenever you install system software, Lucent recommends that you access the unit through the shelf controller serial or LAN port rather than a slot card port.

If your unit is configured with DNIS and CLID passwords, after upgrading from TAOS 9.x to TAOS 10.0.x, the unit will no longer recognize the `dnis-password` and `clid-password` values that were set in prior releases and dial-in users may experience a busy tone.

Saving the system configuration

As a general practice, always save the system configuration before upgrading or downgrading system software. If you use TFTP to save the system configuration, the target file must exist on the TFTP server and you must have permission to write it. For example, the following commands executed on a TFTP server create a target file and set its permissions:

```
$ touch /tftpboot/config/testcfg.1
```

```
$ chmod a=rw /tftpboot/config/testcfg.1
```

Before you save the system configuration, you must enable the `allow-password` permission in the User profile to save the configured passwords. If you do not have `allow-password` permission enabled, you will be prompted to confirm that you wish to save the configuration without passwords. If you do so and then restore the saved configuration, all passwords in the configuration are wiped out. The following commands executed on the APX 1000 or MAX TNT unit save the system's configuration to the target file on the TFTP server and then restore the saved configuration:

```
admin> save network 10.10.10.10 config/testcfg.1
```

```
admin> load config network 10.10.10.10 config/testcfg.1
```



Note For additional information about the `save` command and its options, see the *APX 8000/MAX TNT Reference*.

APX 1000 and MAX TNT upgrade instructions

These instructions show how to upgrade to TAOS 10.0.3 from TAOS version 9.0 or later. If you are not sure which version the system is running, enter the `version` command:

```
admin> version
Software version 9.0.1
```

Note Under certain conditions, the `load tar` command might recognize no slot cards and load only the shelf controller image during the upgrade procedure. If this occurs, reset the system and load the tar file again. The second `load tar` command will load the appropriate slot-card images for the system.

Before you begin upgrading

Before you begin the upgrade procedure, follow these preliminary steps:

1. **Log into the system and save its configuration to a TFTP server.**

   This step is optional but strongly recommended. For details, see "Saving the system configuration" on page 1-9.

2. **Verify that the `load-select` profile is configured to either automatically load only required binaries or to load only selected binaries.**

Upgrading an APX 1000 or MAX TNT unit

Caution The following steps are order sensitive. To help ensure a smooth upgrade, first perform the preliminary upgrade steps described in the preceding section, and then perform the following steps in the order in which they are shown.

To upgrade a standalone unit, proceed as follows:

1. **Format the flash card (optional).**

   For example:

   ```
   admin> format flash-card-1
   ```

2. **Load the boot loader.**

   For example:

   ```
   admin> load boot-sr network 10.10.10.10 tntsrb.bin
   ```

   Note If you upgrade from TAOS 9.0 or higher, continue with step 4. Otherwise, continue with step 3.

3. **Load the tar file.**

   For example:

   ```
   admin> load tar network 10.10.10.10 tntrel.tar
   ```

   Note Skip step 4 for the APX 1000.

4. **Load the tar file.**

   For example:

   ```
   admin> load tar network 10.10.10.10 tntrel.tar tntrel2.tar
   ```

5 **Restore the system configuration file (optional).**

For example:

```
admin> load config network 10.10.10.10 /tftpboot/config/testcfg
```

Note Use the `ls` and `version` commands to verify that the slot cards on your system have the equivalent file on the flash card. If a slot-card image is missing, continue with step 4; otherwise continue with step 6.

6 **Reset the system as follows:**

```
admin> reset
```

Note In this release, the `dnis-password` parameter in the `password-profile` subprofile of the `external-auth` profile has been changed to `DNIS`.

APX 1000 and MAX TNT downgrade instructions

Because releases are not necessarily backward compatible, Lucent recommends that you always restore a backup configuration made under the previous version or one of its predecessors.

Note If you must downgrade, you must have serial access to the APX 1000 or MAX TNT. See the *MAX TNT TAOS 9.0 Release Notes* at `http://www.lucent.com/support`.

Downgrading an APX 1000 or MAX TNT unit

To restore the previous software version (TAOS 9.0.x, 9.1.x, or 10.0.0), proceed as follows:

1 **Format the flash card.**

For example:

```
admin> format flash-card-1
```

2 **Load the previous version of the boot loader.**

For example:

```
admin> load boot-sr network 10.10.10.10 tntsrb.bin
```

Note If downgrading to a previous software version prior to 9.0, continue with step 3. Otherwise proeed to step 4.

3 **Load the previous version of the tar file.**

For example, to load via TFTP from a local host:

```
admin> load tar network 10.10.10.10 tntrel.tar
```

Note Skip step 4.

4 **Load the previous version of the tar file:**

```
admin> load tar network tntrel.tar tntrel2.tar
```

5 **Clear all profiles by entering the `nvram` command.**

For example:

```
admin> nvram
```

6 **Log into the system via the serial connection. Open the `ip-interface` profile for the shelf controller and set the address.**

For example:

```
admin> read ip-interface { { 1 controller 1 } 0}
IP-INTERFACE/{ { shelf-1 controller 1 } 0 } read

admin> set ip-address = 10.10.10.2/24

admin> write
IP-INTERFACE/{ { shelf-1 controller 1 } 0 } written
```

7 **Load a backup configuration made under the restored software version or one of its predecessors.**

For example:

```
admin> load config network 10.10.10.10 config/801-config
```

8 **Reset the system. This step is required.**

For example:

```
admin> reset
```

Enhancements and Corrections in TAOS 10.0.3

2

TAOS 10.0.3 enhancements 2-13

Problems corrected in TAOS 10.0.3 2-14

TAOS 10.0.3 introduces enhancements and corrects problems from the previous release.

TAOS 10.0.3 enhancements

TAOS 10.0.3 includes the following firmware versions for modem and MultiDSP cards.

Firmware versions for digital modem cards

The Mindspeed (formerly known as Conexant) firmware versions for the MAX TNT Digital Modem slot cards include support for V.90, K56flex, K56plus, and all slower, standard modem speeds. This release includes the following Mindspeed firmware:

- Series56 II Digital Modem slot cards (also called CSM/3, TNT-SL-48MOD-SGL and TNT-SL-48MOD-S-C) support V5.817 firmware.
- Series56 III Digital Modem slot cards (also called CSMV/3, TNT-SL-48MODV3-S-C) support V5.8175 firmware.

Firmware versions for MultiDSP cards

This release includes the following Lucent firmware versions for the MAX TNT MultiDSP slot cards:

- 48-port MultiDSP slot cards (TNTP-SL-ADI-C or TNTV-SL-ADI-C) support Controller V0.1.71, Modem DSP V0.1909.0, and VoIP DSP V3.0.52 Lucent firmware.
- 96-port MultiDSP slot cards (APX8-SL-96DSP) support Controller V0.1.70, Modem DSP V0.1909.0, and VoIP DSP V3.0.52 Lucent firmware.
- 240-port MultiDSP slot card (APX-SL-DSP-3-L) support Controller V0.1.70, Modem DSP V0.1909.0, and VoIP DSP V3.0.52 Lucent firmware.
- 288-port MultiDSP slot card (APX-SL-DSP-3) support Controller V0.1.70, Modem DSP V0.1909.0, and VoIP DSP V3.0.52 Lucent firmware.

Problems corrected in TAOS 10.0.3

Table 2-1 lists change requests that have been resolved in this release.

Table 2-1. Change requests resolved in TAOS 10.0.3 (page 1 of 4)

CR #	Description
6002416	Unit incorrectly generates some periodical accounting records to the RADIUS.
7000068	Occasionally, MAX3000 stops receiving and transmitting packets over SWAN connections.
7006894	MAX 3000 supporting X.75 occasionally resets, generating a Fatal Error 2 message.
7006912	24T1 slot card installed in APX 1000 reset, generating a Fatal Error 40.
7006963	MADD2 card occationally resets, generating a Fatal Error 36 message.
7006934	MIF 'Update remote config' command does not function properly.
7007014	After long uptime, unit fails to send RADIUS accounting records and backoff Q overflows.
7007058	Unit incorrectly reports disconnect code 816 for IPDC modem calls.
7007103	HDLC2 cards reset, generating an Fatal Error 42 message. Warning 179 and Warning 104 messages are also logged
7007108	Ethernet 2 cards bounced, generating a Fatal Error Index: 95.
7007110	For ENET3 ND, SNMP Agent incorrectly reports RFC2233.MIB ojbects ifType = 6 and ifSpeed = 10000000 for 100Mbps-FD operation for 100Mbps-FD operation.
7007150	Some dial-in users do not have their IP address imported in the OSPF LSA database.
7007186	When a "slot -d" is performed on an E1 card, the unit does not send the ASGCP REGistration message, stating that the E1 lines on that slot card are no longer available.
7007269	TNT E1 cards configured for e1-brazil-signaling bounce, generating a Fatal Error Index 95.
7007280	SNMP Configuration Changed Trap does not report the correct username.
7007286	When loading code from BOOT prompt, unit skips the 24t1 card, displaying the message "skipping 24e1-card" message. This problem did not occur when loading tar from admin prompt.

Table 2-1. Change requests resolved in TAOS 10.0.3 (page 2 of 4)

CR #	Description
7007303	Using RADIUS authentication and CHAP, when dialing into a TNT using MP+BACP, a user can bypass 2nd channel authentication when entering a blank password.
7007324	MultiVoice:Gateway does not wait for reception of RCF from Primary, before sending RRQ to Secondary.
7007333	MAX 3000 sends Accounting Log "Acct-Link-Count =0" for Multilink Protocol (MP) sessions
7007351	Unit rejects an incoming v.120 call at the ISDN level, when the incoming Q.931 Setup message contains v.120 Bearer Capatibility and Low-Layer Compatibility (LLC) information.
7007356	Fragmented 1500 byte packets are incorrectly compressed with MS-STAC/MPPC.
7007366	Accounting Log incorrectly reports "NAS-Port-Type"as Async instead of PIAFS.
7007379	'TxData' and 'RxRate' of 'show users' command is incorrectly displayed as 32K for PIAFS2.1 sessions.
7007385	FTP transfers of highly-compressed files (like MP3) over MPPC freeze on both Win98SE and Win2k at about 99% completion.
7007391	Unit applies Terminal server PPP delay to v.120 and x.75 asynch calls with DNIS
7007407	V.92 problems connecting with third-party serial modem.
7007452	MADD2 modems become unusable (get stuck) when in releasing state.
7007499	Whenever a VOIP call is places from a user connected to the Switch(BZ5000) to the TNT, the user does not get the voice announcement expected from the TNT.
7007513	MAX3000 running tbxkh.m30 boots up and incorrectly displays the SWAN slot shown as Not Available.
7007523	Third-party modem problems connecting with v.34 emulation.
7007535	When the unit sends an IP TCP SYN packet to an unreachable TCP port (e.g. 80) on the "open" vrouter interface or system address, the TCP RST ACK reply packet is sent by the unit originating from main router interface.
7007552	Occasionally, unit does not send RADIUS accounting attribute 197 (Ascend Data Rate).

Table 2-1. Change requests resolved in TAOS 10.0.3 (page 3 of 4)

CR #	Description
7007555	Occasionally, T3 card fails, generating a Fatal Error 18.
7007570	IPDC ACCP message not returning optional parameters included in RCCP
7007578	MultiVoice: IPDC:Tag 0X99 (latency) is not being reported
7007586	Frame Relay Direct Backup is not functioning properly.
7007599	With two RADIUS accounting servers configured, the unit also switches over to an undefined third server, sending RADIUS accounting requests to 0.0.0.0.
7007616	RADIUS dial-in user private route not created as configured.
7007632	MultiVoice: RTPQOS Tags 0x91 and 0x9d in ACR are not accurate for call.
7007645	The APX would not support proxy ARP for connected users.
7007667	For a unit support dual shelf controllers, cards in quadrant 4 take several minutes to load at startup.
7007679	PPP Calls between units using bi-directional-auth do not come up. The call hangs at the Call-Connected state and later times out with Disconnect Code 105.
7007692	When upgrading from 9.0.6 to 10.0.2e16, the upgrade to the SNMP manager profiles does not occurr properly.
7007694	24T1 card experiences D channel failure on some lines.
7007741	In RADIUS Accounting Start/Stop packets, the unit does not send IPX attributes.
7007754	Unsupported Codec Accepted in RMPC message for call up on Madd2 card.
7007780	G723 and G729 calls fail in when CLID-AUTH in the answer profile is set to DNIS preferred.
7007801	When TNT receives incoming call with "called party subaddress", 8-T1 card generates a Warning 179 message.
7007897	With Telnet mode set to ASCII, unit does not suppress bit-8.
7007987	Output of control module filterdisp command fails to display <filters present> when using AVP 242 (Ascend-Data-Filter) in RADIUS PAP/CHAP auth accept to apply data filters to wan sessions.

Table 2-1. Change requests resolved in TAOS 10.0.3 (page 4 of 4)

CR #	Description
7008170	Radius accounting registers incorrectly high session times when calls fail.

Enhancements and Corrections in TAOS 10.0.2

3

TAOS 10.0.2 enhancements 3-19

Problems corrected in TAOS 10.0.2 3-23

TAOS 10.0.2 introduces enhancements and corrects problems from the previous release.

TAOS 10.0.2 enhancements

TAOS 10.0.2 includes the following enhancements.

Improved POST diagnostics for slot cards

The power-on and self test (POST) logic has been improved to ensure that the unit detects all defective slot cards.

Firmware versions for digital modem cards

The Mindspeed (formerly known as Conexant) firmware versions for the MAX TNT Digital Modem slot cards include support for V.90, K56flex, K56plus, and all slower, standard modem speeds. This release includes the following Mindspeed firmware:

- Series56 II Digital Modem slot cards (also called CSM/3, TNT-SL-48MOD-SGL and TNT-SL-48MOD-S-C) support V5.817 firmware.
- Series56 III Digital Modem slot cards (also called CSMV/3, TNT-SL-48MODV3-S-C) support V5.8175 firmware.

Firmware versions for MultiDSP cards

This release includes the following Lucent firmware versions for the MAX TNT MultiDSP slot cards:

- 48-port MultiDSP slot cards (TNTP-SL-ADI-C or TNTV-SL-ADI-C) support Controller V0.1.69, Modem DSP V0.1908.0, and VoIP DSP V3.0.51 Lucent firmware.
- 96-port MultiDSP slot cards (APX8-SL-96DSP) support Controller V0.1.69, Modem DSP V0.1908.0, and VoIP DSP V3.0.51 Lucent firmware.
- 240-port MultiDSP slot card (APX-SL-DSP-3-L) support Controller V0.1.69, Modem DSP V0.1908.0, and VoIP DSP V3.0.51 Lucent firmware.

- 288-port MultiDSP slot card (APX-SL-DSP-3) support Controller V0.1.69, Modem DSP V0.1908.0, and VoIP DSP V3.0.51 Lucent firmware.

Enhanced VoIP signaling

EOI#: 65233

Lucent units affected: APX, TNT

Feature ID: n/a

Introduced in: r10_0

EOI engineer(s): Shichang Liu (sliu@ascend.com

Edited by: sara shopkow

Written by: jozef wroblewski

Destination document(s): VOIP

The command line interface (CLI) help text for `fast-proceeding` has been improved. You can use the `fast-signaling` parameter in the `voip` profile to avoid H.225 and T303 timer timeouts between H.323 endpoints on the E1 ingress gateway.

Normally, when egress has a slow inband signaling line, a signal to let the call proceed is sent to the ingress side after a long inband signaling cycle. Sometimes the delay results in H.225 and T.303 timer timeouts on the ingress side, and the call is dropped. By setting `signaling-model` to `fast-proceeding`, the egress gateway sends an H.225 signal to allow the call to proceed after setup with an Admission Request (ARQ) message, thus avoiding H.225 and T.303 timere time-outs on ingress. For example, to to cause the egress gateway to send an H.225 signal to allow calls to proceed after setup with ARQ, set `signaling-model` as follows:

```
[in VOIP/{ 0 0 }]
admin> set signaling-model = fast-proceeding
```

Reference entries

`signaling-model`

Description Specifies the type of signaling to be used between H323 end points.

Usage For a line between H.323 endpoints, specify one of the following:

- `early-alerting`—Specifies that an alert message is sent with inband signaling.
- `slow-proceeding`—Specifies that an alert is sent to let the call proceed with inband signaling.
- `fast-proceeding`—Specifies that an H.225 signal is sent to let the call proceed with an Admission Request (ARQ) message. On an egress gateway with slow inband signaling, such as an E1 line with R2 signaling, use this setting to avoid ingress side H.225 and T303 timer timeouts.

Example `set signaling-model = fast-proceeding`

Location `VOIP`

IP-within-IP security enhanced

Lucent units affected: APX 1000, APX 8000, MAX TNT

Feature ID: NA

Introduced in: TAOS APX, TNTfor 10.0

EOI engineer(s): Deepak Srivastava (ds113@ascend.com)

Edited by: Sara

Written by: jozef wroblewski

Lucent units affected: WAN Routing and Tunneling Guide

With IP-within-IP Enapsulation Protocol (IPIP) enabled, all IPIP packets received by the TAOS unit that are addressed to local IP addresses are decapsulated. This presents a potential security problem.

A new subprofile in the `ip-global` profile, `ipinip-options`, provides the option to disallow decapsulation. The subprofile, `ipinip-options` contains the single parameter, `decapsulation-enable`. To prevent decapsulation of IPIP packets addressed to local IP addresses, use the default setting (`decapsulation-enable = no`). Decapsulation of IPIP packets is allowed only if `decapsulation-enable` is set to `yes`. For example:

```
admin> list ipinip-options
[in IP-GLOBAL:ipinip-options]
decapsulation-enable = no
admin> set decapsulation-enable = yes
```

The software decapsulates IPIP packets only if you purchase the license for the IPIP protocol.

Reference entries

IPinIP

Description A subprofile that contains a parameter to control decapsulation of IP-within-IP Encapsulation Protocol (IPIP) packets.

Usage Following is a listing of the `ipinip-options` subprofile with the default setting:

```
[in IP-GLOBAL:ipinip-options]
decapsulation-enable = no
```

Location `IP-GLOBAL`

decapsulation-enable

Description Specifies whether decapsulation is performed on IP-within-IP Encapsulation Protocol (IPIP) packets addressed to local IP addresses on the TAOS unit.

Usage Specify one of the following settings:

- `yes` specifies that decapsulation of IPIP packets is done.
- `no` (the default) specifies that IPIP packets are not decapsulated.

Example `set decapsulation-enable = yes`

Location `IP-GLOBAL`

Log profile enhanced

Lucent units affected: APX,TNT

EOI#: 2000195

Feature ID: n/a

Introduced in: 10.0.2c0

EOI engineer(s): Pratul Goyal (pratulg@ascend.com)

Edited by: Sara

Written by: jozef wroblewski

Destination document(s): Admin Guide

A new parameter, `log-tunnel-progress`, has been added to the `log` profile. The `log-tunnel-progress` parameter enables or disables the generation of Layer 2 Tunneling Protocol (L2TP) syslog messages, and thus can prevent the risk of L2TP messages exceeding the capacity of syslog servers.

To disable sending L2TP syslog messages to the syslog server, set `log-tunnel-progress` to `no` (`yes` is the default). For example:

```
[in LOG]
save-level = debug
save-number = 100
software-debug = no
call-info = end-of-call
syslog-enabled = no
host = 0.0.0.0
port = 514
facility = local0
syslog-format = tnt
log-call-progress = yes
log-tunnel-progress = yes
log-software-version = no
syslog-level = info
auxiliary-syslog = [ { no info 0.0.0.0 514 local0 } { no info 0.0.0.0 514
local+
```

```
admin> set log-tunnel-progress = no
```

Reference entries

`log-tunnel-progress`

Description Specifies whether the syslog-related messages generated while processing a tunneled call are sent to the syslog server.

Usage Specify one of the following:

- `yes` (the default)—L2TP tunnel-related messages are sent to the syslog server.
- `no`—L2TP tunnel-related messages are not sent to the syslog server.

Location `LOG`

Problems corrected in TAOS 10.0.2

Table 3-1 lists change requests that have been resolved in this release.

Table 3-1. Change requests resolved in TAOS 10.0.2 (page 1 of 3)

CR #	Description
6000646	The Digital Modem slot card was limited to v.23 modulation using the `AT-Answer-String` setting `+MS=3;`. MultiDSP firmware upgraded to V0.1.69. See "Firmware versions for MultiDSP cards" on page 3-19.)
6002020	The SS7 COT tests did not conform to the specification.
7006599	TAOS units were not performing checkpointing for HDLC-NRM as specified.
7006648	The `framed-ipx-network` value was reversed when a radius accounting START/STOP packet was sent across to the RADIUS server.
7006666	L2TP tunnel calls were completely logged during a Wan open debug session, causing a data lost statement to overide a needed Wan open debug.
7006685	In a short-duration transaction network (SDTN), 0.2 percent of data packets were lost on the TAOS unit. When the terminal dialed up and proceeded to do its transaction, it timed out waiting for the I-frame to be transmitted from the TAOS unit.
7006816	IP packets were received and routed via Fast path, but the corresponding IP cache and IP port cache statistics were not updated.
7006867	The pseudo route functionality was not working on the MAX TNT.
7006914	Increased timeouts on IPDC messages were seen while doing a TFTP upgrade of the software.
7006924	A consistent FE 29 occured on the ingress HDLC resource card when the `filterdisp` *`id`* command was issued.
7006961	The APX 1000 was generating a Warning 800 on the MultiDSP slot card.
7006964	The TAOS unit was not copying the software from one controller to the other.

Table 3-1. Change requests resolved in TAOS 10.0.2 (page 2 of 3)

CR #	Description
7007004	During stress conditions (maximum calls connected), when the `filterdisp` command was used to view all the filters associated with active calls on the TAOS unit, sessions were reported to have filters when no filters were present.
7007016	On CSM3V and HDLC2 cards, binary FTP transfers were suspended when there was a combination of a V.120 PPP mobile connection and a user rate of 19.2 or 28.8Kbps.
7007050	In Japan, there was a high percentage of no-carrier calls on MultiDSP slot cards compared to Digital Modem slot cards. MultiDSP firmware upgraded to V0.1.69. See "Firmware versions for MultiDSP cards" on page 3-19.)
7007051	The quick-connect (QC) was not efficient on Olitec Speed Com V6.106 and USR 56K Fax. MultiDSP firmware upgraded to V0.1.69. See "Firmware versions for MultiDSP cards" on page 3-19.)
7007053	L2F tunneling did not work when the APX 8000 was used as a network access server (NAS).
7007085	On the MultiDPS slot card there was a high packet latency (about 1 to 3 second delay) every 20 seconds at low speed v.34 modulation when symmetrical transmit and receive speeds were less than 24.Kbps. MultiDSP firmware upgraded to V0.1.69. See "Firmware versions for MultiDSP cards" on page 3-19.)
7007086	Configuration errors could not be caught because there was no indication of the requested incoming port in the messages sent to syslog or RADIUS.
7007096	A memory buffer was being freed twice, or incorrectly, causing digital modem cards to reboot every two minutes with W104, W179, W150 and FE1, FE8, FE29 errors.
7007104	The cancellation of voice announcements was not successful when the cancellation request was sent within 50 milliseconds after sending the actual request for playing the announcement.
7007153	The `call-log-key` and `shared-secret` were still visible when `allow-password` was set to `no`.
7007154	When `default-status` was set to `yes` in the `user` profile and initial line status showed `No lines available`, users dialing in had to type the `stat` command twice to recover.
7007159	After there was a switch to the redundant controller and IP Device Control (IPDC) link backup had taken place, calls were rejected for six to eight seconds.

Table 3-1. Change requests resolved in TAOS 10.0.2 (page 3 of 3)

CR #	Description
7007221	Data filters were not being applied when only a DNIS profile was defined on RADIUS and no other connection or user profile was defined (locally or on RADIUS).
N/A	Calls were being dropped between H.323 end points because of a slow inband signaling line. See "Enhanced VoIP signaling" on page 3-20.
N/A	Users were restricted to configuring a single community per summarization profile.
N/A	The prefix part of the Border Gateway Protocol (BGP) policy did not match the prefix defined in summarization. The user was not given the option to configure the `prefix`, `prefix-exactly` and `prefix-longer-than` parameters in the `if` part of the rules of the BGP `summarization-policy`.
N/A	IPIP decapsulation of IP packets sent to local IP addresses presented a potential security problem. See "IP-within-IP security enhanced" on page 3-21.
N/A	L2TP syslog messages were exceeding the capacity of syslog servers. See "Log profile enhanced" on page 3-22.
N/A	When there was an error testing segmentation and reassembly (SAR) control memory when bringing a slot card to the `up` state, an error message was logged but the slot card still entered the `up` state.

Enhancements and Corrections in TAOS 10.0.1

4

TAOS 10.0.1 introduces enhancements and corrects problems from the previous release.

TAOS 10.0.1 enhancements

TAOS 10.0.1 includes the following enhancements.

Firmware versions for digital modem cards

The Mindspeed (formerly known as Conexant) firmware versions for the MAX TNT Digital Modem slot cards include support for V.90, K56flex, K56plus, and all slower, standard modem speeds. This release includes the following Mindspeed firmware:

- Series56 II Digital Modem slot cards (also called CSM/3, TNT-SL-48MOD-SGL and TNT-SL-48MOD-S-C) support V5.817 firmware.
- Series56 III Digital Modem slot cards (also called CSMV/3, TNT-SL-48MODV3-S-C) support V5.8175 firmware.

Firmware versions for MultiDSP cards

This release includes the following Lucent firmware versions for the MAX TNT MultiDSP slot cards:

- 48-port MultiDSP slot cards (TNTP-SL-ADI-C or TNTV-SL-ADI-C) support Controller V0.1.66, Modem DSP V0.1905.0, and VoIP DSP V3.0.51 Lucent firmware.
- 96-port MultiDSP slot cards (APX8-SL-96DSP) support Controller V0.1.66, Modem DSP V0.1905.0, and VoIP DSP V3.0.51 Lucent firmware.
- 240-port MultiDSP slot card (APX-SL-DSP-3-L)support Controller V0.1.66, Modem DSP V0.1905.0, and VoIP DSP V3.0.51 Lucent firmware.
- 288-port MultiDSP slot card (APX-SL-DSP-3)support Controller V0.1.66, Modem DSP V0.1905.0, and VoIP DSP V3.0.51 Lucent firmware.

Support for the 288-port and 240-port MultiDSP card

TAOS 10.0.1 supports the 288-port MultiDSP slot card (APX-SL-DSP-3) and the 240-port MultiDSP slot card (APX-SL-DSP-3-L) on the APX 8000 and APX 1000. For complete information about the 288-port and 240-port MultiDSP card for the APX 8000, see the *MultiDSP Slot Gard Guide for APX 8000*. For information about enhancements to the 288-port and 240-port MultiDSP card for the APX 1000, see the TAOS 10.0.0 Release Note. These documents are available at `http:www.lucent.com/support`.

Support for the APX Ethernet slot card

The APX Ethernet slot card for APX 1000, APX 8000, and MAX TNT units has two full-duplex 10/100Mbps Ethernet ports with a high packet-per-second throughput to support Voice over IP (VoIP). An APX Ethernet card supports autonegotiation: Ethernet devices exchange information and agree on a communication speed and duplex mode.

For complete information about the APX Ethernet card, see the *APX™/MAX TNT® Ethernet Slot Card Guide*, available at `http:www.lucent.com/support`.

Problems corrected in TAOS 10.0.1

Table 4-1lists change requests that have been resolved in this release.

Table 4-1. Change request resolved in TAOS 10.0.1

CR #	Description
N/A	The following features were not supported on the 288-port MultiDSP slot card (APX-SL-DSP-3) and the 240-port MultiDSP slot card (APX-SL-DSP-3-L): n IP in IP n Modem call logging n Synchronous TCP-clear n V.92 quick connect and modem on hold
N/A	Forty percent of calls on TAOS units were connecting at only 1200bps.

Notices, Known Issues, and Caveats in TAOS 10.0.3

5

Notices in TAOS 10.0.3. 5-29

Known issues in TAOS 10.0.3 5-34

Caveats in TAOS 10.0.3 5-35

Notices in TAOS 10.0.3

The following notices provide important information regarding TAOS 10.0.3 software and hardware.

Notice of TAOS license and upgrade changes

Starting with the release of TAOS 9.1, the following changes are now in effect for TAOS base software and TAOS software upgrades, service, and maintenance.

Notice concerning APX 8000 redundant synchronization

On an APX 8000 with dual shelf controllers, the redundant synchronization feature is disabled by default. To obtain a software license for this feature (APX8-SO-SCR) at no charge, contact Lucent OnLine Customer Support at `http://www.lucent.com/support`.

If you are not sure whether redundant synchronization is licensed for your software, access the base profile with the following command:

```
admin> get base redundant-sync-enabled
[in BASE:redundant-sync-enabled]
redundant-sync-enabled = no
```

The system sets this parameter to `yes` when the license is installed.

Price change for base TAOS software

With the release of the TAOS 9.1, MAX™ 3000, MAX™ 6000, MAX TNT, and APX 8000 hardware and TAOS software are priced separately. The TAOS software license is now a mandatory item for any new order. The license grants licensees the right to use the base TAOS 9.1 software on the specific platform purchased.



Note The right to upgrade to a subsequent TAOS minor or major software release that includes new operating system software enhancements is no longer included as part of the base TAOS software license.

Price change for upgrades and maintenance to TAOS 10.0.3 software

Upgrades to TAOS 10.0.3 software and subsequent releases for the MAX™ 3000, MAX™ 6000, MAX TNT, APX 1000, and APX 8000 platforms are available through Lucent Worldwide Services as part of an annual software maintenance contract. These contracts are priced separately for each platform and include the following software and services:

- TAOS software updates, upgrades, and support
- TAOS software options (or *hash codes*), updates, upgrades, and support
- Remote technical support
- Hardware maintenance and return



Note Only customers with an established software maintenance contract are authorized to upgrade designated TAOS-enabled units to TAOS 10.0.3 and to download the required TAOS 10.0.3 software files.

Distribution change for TAOS 10.0.3 software

TAOS 10.0.3 and subsequent general-availability TAOS software releases are no longer available from `ftp.ascend.com`. Upgrades to TAOS 10.0.3 and all subsequent releases and updates (maintenance releases) are available instead from the Lucent OnLine Customer Support at `http://www.lucent.com/support`.

TAOS software license agreement change

Lucent Technologies is introducing a new software license agreement that grants you a personal, nontransferable, nonexclusive right to use TAOS 10.0.3 in object code form only, and its accompanying documentation. The agreement prohibits you from loading or using TAOS software on any unit of Lucent equipment other than the unit for which you purchased the software, unless otherwise agreed upon in writing by Lucent.

Use of TAOS software on any equipment other than that for which it was obtained, or any material breach of these conditions, immediately and automatically terminates the license. Lucent reserves the right to pursue all available legal remedies to enforce the terms and conditions of the software license.

Notice of discontinued support for multishelf functionality

Multishelf functionality is not supported in TAOS 10.0.3

Notice of parameter name changes in the external-auth profile

In TAOS 8.0, the `dnis-password` and `clid-password` parameters were added to the `external-auth` profile. With these parameters, you were able to set RADIUS passwords for DNIS and CLID preauthentication.

In TAOS 9.0, the `dnis-password` and `clid-password` parameters were moved to the `password` subprofile of the `external-auth` profile. The parameter names were also changed, as shown in the following sample subprofile (shown with default values):

```
[in EXTERNAL-AUTH:password-profile]
clid = Ascend-CLID
dnis = Ascend-DNIS
```

If your unit is configured with DNIS and CLID passwords, after upgrading from TAOS 8.x to TAOS 9.x, the unit no longer recognizes the `dnis-password` and `clid-password` values that were set in prior releases and dial-in users might experience a busy tone.

To restore the DNIS and CLID preauthorization passwords, you must apply the value of the `dnis-password` and `clid-password` parameters (set in earlier TAOS 8.x releases), to the new `dnis` and `clid` parameters as follows:

```
admin> read external-auth
EXTERNAL-AUTH read

admin> set password-profile dnis = secretdnis

admin> set password-profile clid = secretclid

admin> write
EXTERNAL-AUTH written
```

Notice of change in supported values for the signaling mode

After you upgrade an APX or MAX TNT unit that is configured as a MultiVoice gateway, the unit might generate a `bad value` error message for the value assigned to the `signaling-mode` parameter in the `line-config` subprofile of T1 profile. This situation occurs when you upgrade the APX or MAX TNT unit from either of the following limited availability releases to TAOS 10.0.3:

- TAOS 8.0-103.x
- TAOS 8.0-118.x

When these two limited availability releases were compiled, the supported values for the `signaling-mode` parameter were defined as enumerated values, rather than hardcoded values, as is done for MAX 9.0. Applying a saved configuration from either limited availability release to TAOS 9.0 causes the `bad value` error.

To correct this error, you must reset the value of the `signaling-mode` parameter after applying the saved configuration and reinitializing the APX or MAX TNT unit.

Notice about MultiDSP slot cards

In MAX 10.0.3, you can combine 48-port and 96-port MultiDSP slot cards in a MAX unit for V.90 and ISDN dial-up termination.

Notice of TAOS interoperability with SS7 signaling software

APX and MAX TNT units support two separate software licenses for integrating the units into Signaling System 7 (SS7) networks:

- Access SS7 Gateway Control Protocol (ASGCP). This method of integration enables the MAX unit to terminate data calls in an SS7 network. The signaling gateway must be Internet call diversion (ICD) for softswitch (formerly ASG).
- IP Device Control (IPDC) protocol. IPDC is a third-party proprietary protocol. This method of integration enables the MAX unit to terminate both voice and data calls. The signaling gateway can be ICD for softswitch or Lucent Softswitch.

MAX 10.0.3 supports interoperability with sections of IP Device Control (IPDC) 0.15.1, including PRI tunneling.

Notice of discontinuance of configurable RADIUS port and ID space

In MAX 8.x, the default settings for User Datagram Protocol (UDP) source ports and ID spaces for communication with a RADIUS server specified the use of a unique source port for each card and a distinct ID space for both authentication and accounting requests. However, the unit could be configured to use a single source port and ID space systemwide to accommodate certain RADIUS server daemons that had a system-unique requirement.

Because no known RADIUS servers continue to maintain this requirement, and because the unit's port density makes the use of a single port and ID space undesirable, with MAX 10.0.3, the MAX unit always uses port-unique source ports and always sends RADIUS authentication and accounting requests with distinct RADIUS IDs. The following parameters are therefore no longer supported and have been removed from the `external-auth` profile:

```
[EXTERNAL-AUTH]
rad-id-space = distinct
rad-id-source-unique = port-unique
```



Note The `rad-ip-space` and `rad-id-source-unique` parameters no longer appear in the `external-auth` profile with TAOS 10.0.3. If you downgrade the unit to an earlier release, the parameters revert to their default values for that release.

Notice of discontinuance of software support

Software support has been discontinued for the APX and MAX TNT Ethernet-0 slot card (TNT-SL-E10), the Fast (100MB) Ethernet-1 slot card (TNT-SL-E100), and the older APX or MAX TNT Hybrid Access slot cards (TNT-SL-HA128 and TNT-SL-HA192).

Notice of deprecated management features

Use of the `if-admin` diagnostic command is deprecated. The functionality that was provided by the `-d` (down) and `-u` (up) options of the command is now provided by `read`, `set`, and `write` operations on one of the following profiles:

- The `admin-state-perm-if` profile for permanent interfaces such as a nailed interface
- The `admin-state-phys-if` profile for physical interfaces such as a T1 line

The other options of the `if-admin` command are not supported.

Use of the `call-log-radius-compat` parameter in the `call-logging` profile is deprecated in this software version.

The `callActiveIfIndex` and `callStatusIfIndex` objects in the call MIB are not supported in this software version.

This following objects are no longer supported in this software version:

- The `lmodem.mib`
- The `resetStat` group in `ascend.mib`
- The `consoleTable`, `doTable`, and `hostStatusTable` in `ascend.mib`

Notice of discontinuance of support for AppleTalk and ARA routing

MAX 10.0.3 does not support for AppleTalk, which includes the AppleTalk Remote Access Protocol (ARAP) and AppleTalk Control Protocol (ATCP) for the MAX unit.

A MAX unit can no longer act as an AppleTalk router, but a Macintosh workstation can continue to access the Internet and IP-based services by means of the MAX unit.

This release discontinues support for the following profiles and subprofiles that are associated with AppleTalk and AppleTalk Remote Access (ARA):

- `atalk-global` profile
- `atalk-interface` profile
- `answer-defaults:ara-answer` subprofile
- `connection:ara-options` subprofile
- `connection:appletalk-options` subprofile

In addition, in the `connection` profile, the `encapsulation-protocol` parameter can no longer be set to `ara`.

Notice concerning call signaling support on T1/E1 slot cards

When configuring call signaling support on E1 trunks:

- Do not configure R1/R2 multifrequency signaling and R2 Dual-Tone Multifrequency (DTMF) signaling for different trunks on the same E1 slot card.
- When configuring call signaling on E1 trunks, the MAX unit loads only one tone look-up table per slot card. The tone look-up tables for R1/R2 MF and R2 DTMF signaling are unique to the call signaling type specified by the `signaling-mode` parameter. The multifrequency tone look-up table will not support DTMF signaling, and the DTMF tone look-up table will not support R1/R2 multifrequency signaling.

When configuring call signaling support on T1 trunks:

- You can configure ISDN and Feature Group D (FGD) signaling for different trunks on the same T1 slot card.
- Do not configure inband, robbed-bit signaling and Feature Group D (FGD) signaling for different trunks on the same T1 slot card. The tone look-up tables for FGD are unique to the call signaling requirements for Access Tandem switching.
- Do not configure inband multifrequency signaling and inband Dual-Tone Multifrequency (DTMF) signaling for different trunks on the same T1 slot card. The tone look-up tables are unique to the call signaling type specified by the `signaling-mode` parameter. The multifrequency tone look-up table will not support DTMF signaling, and the DTMF tone look-up table will not support multifrequency signaling.

Known issues in TAOS 10.0.3

The following known issues affect TAOS 10.0.3 software and hardware:

Known issue using multiple OC3-ATM2 slot cards

If multiple OC3-ATM2 slot cards are configured for OC3 ingress, traffic is unable to pass through the egress slot card.

Known issue sorting call routing types

The new approach for finding a call routing destination device can be done in two steps. The first stage identifies the best-fit destination slot, which is based on the nature of the call and the specific call-route profiles. The second stage identifies the best-fit device within that specific slot. The new approach distributes the call-routing algorithm to the slot cards, instead of keeping it centralized on the shelf controller. In this manner, the source slot selects the destination slot (based on the `call-route` profiles) and the destination slot card selects the destination device of the call route (based on `call-route` profiles).

This is a performance change. When a calls comes in, the shelf controller has to do time-critical work to identify where the call should go. This new scheme lets the shelf controller choose the best slot card, and that slot selects a port on the card to handle the call.

Known issue receiving warning messages when saving profiles

From memory, if you modify `call-route` profiles while the system is taking calls, you may receive occasional warning messages (W179).

Known issue handling full BGP Internet routing table

The TAOS unit may not route reliably if Border Gateway Protocol (BGP) is set to accept and inject the full Internet routing table (which currently consists of approximately 92,000 routes). Since the TAOS units are not designed to be full-fledged Internet core routers, this is not considered to be a major problem. In order to prevent this situation, future versions may have an explicit limit beyond which the unit will not accept additional routes. It is currently recommended that you set BGP to accept a limited number of routes if it would otherwise be receiving too large a routing table.

Known issue with 96-port MultiDSP slot card

When using the G.711 audio codec, Lucent recommends NOT to use two frames per packet when you expect to have a fully loaded network with 96 active calls. You should do one of the following:

- Set the `frames-per-packet` parameter to 4 or higher in the `Voip` profile.
- Leave `frames-per-packet` set to 2 (the default), but disable DSPs on the card with the `mdmdisable` command. (Issue the `? mdmdisable` command for help on this command.)

```
admin> mdmdisable 1 5 73 24
disable DSPs from 73 - 96
```

To reenable the DSPs, use the `mdmenable` command.

```
admin> mdmenable 1 5 73 24

enable DSPs from 73 - 96
```

The DSPs will remain disabled, even after you reset the chassis. If `2 Frames Per Packet` are maintained and the DSPs are not disabled, voice quality may become degraded after approximately 80 active calls.

Caveats in TAOS 10.0.3

The following caveats apply to TAOS 10.0.3:

- Hot-standby redundancy was a new feature in 10.0.0. There are known issues with this feature that are being addressed in upcoming maintenance releases. In particular, shelf controller failovers on a hot-standby system in a high call rate environment (that is, a large number of calls per second) might exhibit these issues. In addition, rapid failovers from one shelf controller to the other might also trigger these issues. Failovers of a hot-standby system in an environment with typical call rates and infrequent switchovers are operational.
- When a long-term loss of communication to a RADIUS or call-logging server occurs (which results in loss of data), the MAX TNT unit reports the event by generating a Warning 104 message.
- When you attempt to initiate terminal services such as TCP-clear, Rlogin, or Telnet using a scripted login, the MAX unit might occasionally terminate calls abnormally, displaying a cause code 51 and progress code 40 in `syslog` or RADIUS accounting records. This issue is aggravated by scripted logins when the responses are entered before the MAX TNT unit prompts for input.
- Before changing an ATM connection's VPI-VCI assignment, you must disable the connection on a OC3 (Copper) ATM slot card (TNT-SL-OC3-C) or OC3 (Fibre) ATM slot card (TNT-SL-OC3-F).
- Multilink Protocol bonding of analog calls is supported, but some client modems and software may have compatibility problems.
- Configurable receive and transmit data rate limits are not supported on the unchannelized DS3-ATM slot card (TNT-SL-UDS3A). Configurable receive and transmit data rate limits *are* supported on the unchannelized DS3 frame relay slot card (TNT-SL-UDS3).
- The `lan-modem` profiles contain entries for 96 devices. For the 96-port MultiDSP slot card, all 96 entries in the profile are used. For 48-port Digital Modem cards—Series56 (TNT-SL-48MOD-S56), Series56 II (TNT-SL-48MOD-S-C), and Series56 III (TNT-SL-48MODV3-S-C)—only the first 48 entries are used. For the 48-port MultiDSP card (TNTP-SL-ADI-C or TNTV-SL-ADI-C), every other entry in a LAN-Modem profile is used (odd ports only, from 1 to 95).
- Virtual path shaping is supported on first-generation slot cards only. This feature is not supported on second-generation OC3-ATM and DS3-ATM cards.
- When using a MultiDSP slot card and the IPDC protocol to generate remote country-specific call progress tones (for example, dial tone, alerting, busy, network busy and unobtainable), the ability to send the country tag locally in the NSUP is no longer supported.
- The Internetwork Packet Exchange (IPX) protocol is not supported in this release.

- Calls of the following types are disconnected when APX 8000 units switch from the primary to the secondary shelf controller. All other calls will stay up. Profiles and parameters in the user interface related to these call types have not been tested and are not supported in this release.
  - BACP
  - CBCP
  - Multilink frame relay (MFR)
  - PHS on MultiDSP
  - Route to multiple FR PVCs on NI
  - frame relay SVCs
  - ATM SVCs
  - ASGCP
  - PPTP
  - ATMP
  - L2TP dial-out calls
  - X.25
  - X.75
  - SLIP
  - CLSLIP
  - Multicast