



849 NW State Road 45
PO Box 370
Newberry, FL 32669

TEST REPORT

STANDARD (s):

**FCC Part 15, Subparts B, C, and D
IC RSS-213 & ICES-003
UPCS / LE-PCS Isochronous Device
Base & Handset: 1921.536 – 1928.448 MHz
ANSI C63.17 - 1998 (or 2005 Draft where applicable)
ANSI C63.4 – 2003**

APPLICANT:

ASCALADE TECHNOLOGIES INC.
12051 RIVERSIDE WAY
RICHMOND, BC V6W 1K7 V6W 1K7
Tel.: 1-604-241-7991
MR. KEVIN YAU, QUALITY MANAGER

MODEL NUMBERS:

VOIP3211S/17

**DESCRIPTION OF
PRODUCT:**

1.9 GHz DECT USB/POTS TELEPHONE

FCC IDs:

PBWB187R26 (BASE)
PBWB187R26H (HANDSET)

IC:

3842A-B187

**DATE SAMPLE
RECEIVED FOR TESTING:**

2/16/2006

DATE TESTED:

3/03/2006

TEST RESULTS:

☒ PASS ☐ FAIL

PLEASE NOTE: THE ATTACHED REPORT SHALL NOT BE REPRODUCED EXCEPT IN FULL WITHOUT THE WRITTEN APPROVAL OF TIMCO ENGINEERING, INC.

TABLE OF CONTENTS

1	GENERAL INFORMATION	1
1.1	COMPLIANCE STATEMENT:	1
1.2	EQUIPMENT UNDER TEST SPECIFICATION	2
1.2.1	TRANSMITTER TECHNICAL CHARACTERISTICS	2
1.2.2	POWER SOURCE (S)	2
1.3	RATIONAL FOR SELECTING TEST CONFIGURATION(S):.....	2
1.4	DESCRIPTION ON HOW THE EUT WAS EXERCISED DURING TESTING:2	
1.5	TEST STANDARDS	3
2	TEST ENVIRONEMENT	3
3	TEST RESULTS	4
3.1	RADIATED PEAK TRANSMIT POWER.....	4
3.1.1	BASE:	5
3.1.2	HANDSET:	6
3.1.3	BASE TRANSMITTER SPURIOUS EMISSIONS :	7
3.1.4	HANDSET TRANSMITTER SPURIOUS EMISSIONS :	8
3.2	GENERAL RADIATED SPURIOUS EMISSIONS	9
3.2.1	RADIATED SPURIOUS EMISSIONS	9
3.2.2	BASE in STAND-BY MODE:.....	10
3.2.3	HANDSET IN STAND-BY MODE:	10
3.2.4	AC POWER LINES CONDUCTED SPURIOUS EMISSIONS:11	
4	TEST EQUIPMENT AND ANCILLARIES USED FOR TESTS.....	16
5	TEST SETUP PHOTOGRAPHS	17
6	EUT EXTERNAL PHOTOGRAPHS	20
7	EUT INTERNAL PHOTOGRAPHS	20
8	LABEL PHOTOGRAPHS	20

APPLICANT: ASCALADE TECHNOLOGIES INC.

FCC ID: PBWB187R26H

MODEL #: VOIP3211S/17

REPORT #: A\ASCALADE\321AUT6\321AUT6TestReport.doc

1 GENERAL INFORMATION

The test results relate only to the items tested.

1.1 COMPLIANCE STATEMENT:

This equipment has been tested in accordance with the standards identified in this test report. To the best of my knowledge and belief, these tests were performed using the measurement procedures described in this report and demonstrate that the equipment complies with the appropriate standards. No modifications were made to the equipment during testing in order to demonstrate compliance with these standards.

I attest that the necessary measurements were made, under my supervision, at TIMCO ENGINEERING, INC. located at 849 N.W. State Road 45, Newberry, Florida 32669.

Authorized Signatory Name: MARIO R. DE ARANZETA

Signature: <ON FILE>

Function: ENGINEER

Date: 4/10/2006

Test engineer name: NAM NGUYEN

Signature: <ON FILE>

Date: 4/10/2006

APPLICANT: ASCALADE TECHNOLOGIES INC.

FCC ID: PBWB187R26H

MODEL #: VOIP3211S/17

REPORT #: V:\A\Ascalade\321AUT6\321AUT6REVTestReport.doc

1.2 EQUIPMENT UNDER TEST SPECIFICATION

Characterization of test item:

Prototype ☒
Pre-production ☐
Production ☐

Construction of equipment:

☒ Single unit
☐ Multiple units (If multiple units describe each one clearly)

TYPE OF EQUIPMENT:

Fixed ☐
Mobile ☐
Portable Station ☐

X	Transmitter		Simplex	X	Integral antenna (Handset and Base)
	Receiver	X	Duplex		Single antenna connector
	Transceiver				Two antenna connector
X	Battery charger				Vehicle battery adaptor
	Remote Control Head				

1.2.1 TRANSMITTER TECHNICAL CHARACTERISTICS

FREQUENCY CHARACTERISTICS (Method of frequency generation):

CRYSTAL ☐ SYNTHESIZER ☒ OTHER ☐

State the maximum number of channels over which the equipment can operate:_____

MAXIMUM RATED TRANSMITTER OUTPUT POWER: 0.119W for the Base and 0.116W for the Handset.

1.2.2 POWER SOURCE (S)

AC SUPPLY: State voltage: _____ Single phase: ____ Three phase: ____

AC SUPPLY FREQUENCY (Hz) _____

EXTERNAL DC SUPPLY: Nominal voltage __2.4VDC NiMH rechargeable battery for Handset and 9VDC via a power adapter for Base

BATTERY: Nickel Cadmium ☒ Lead acid ☐ Leclanche ☐ Lithium ☐

1.3 RATIONAL FOR SELECTING TEST CONFIGURATION(S):

No deviation from technical specifications

1.4 DESCRIPTION ON HOW THE EUT WAS EXERCISED DURING TESTING:

(e.g software description, test signal, etc.)
The EUT was set in continuous transmit mode of operation.

APPLICANT: ASCALADE TECHNOLOGIES INC.

FCC ID: PBWB187R26H

MODEL #: VOIP3211S/17

REPORT #: V:\A\Ascalade\321AUT6\321AUT6REVTestReport.doc

1.5 TEST STANDARDS

FCC Part 15, Subparts B, C, and D
IC RSS-213 & ICES-003
UPCS / LE-PCS Isochronous Device
Base & Handset: 1921.536 – 1928.448 MHz
ANSI C63.17 - 1998 (or 2005 Draft where applicable)
ANSI C63.4 - 2003

2 TEST ENVIRONEMENT

Temperature

Normal test temperature (Tnom): 22 °C
Extreme test temperatures (Tmax): n/a °C
(Tmin): n/a °C

Relative Humidity 50 %

Details of power supply

Normal test voltage Handset (Vnom): 2.4 ____ VDC
Base (Vnom): 9 ____ VDC (from adapter)

Extreme test voltage (Vmax): ____ VDC
(Vmin): ____ VDC

APPLICANT: ASCALADE TECHNOLOGIES INC.
FCC ID: PBWB187R26H
MODEL #: VOIP3211S/17
REPORT #: V:\A\Ascalade\321AUT6\321AUT6REVTestReport.doc

3 TEST RESULTS

3.1 RADIATED PEAK TRANSMIT POWER

Clause: 15.319 (c)

Test procedure: ANSI C63.17 section 6.1.2

Technical requirements/Limits:

The peak transmit power shall not exceed 100 μ W multiplied by the square root of the emission bandwidth in hertz measured at 26dBc.

The measured emissions bandwidth is 1.5 MHz max

Limit = $100\mu\text{W} * \sqrt{(\text{BW in Hz})} = 0.122\text{W} = 20.8 \text{ dBm}$

and Radiated limit $\leq 118.8 \text{ dB}\mu\text{V/m}$ at 3m by radiated measurement derived from Friis formula as follows $P = (E*d)^2/30G$, where $P = 0.122 \text{ W} = 20.8 \text{ dBm}$

This assumes a $G = \text{Numeric gain of TX antenna} = 1.585$ (2.0 dBi) worst-case across band
 $d = 3 \text{ m}$

Notes: The calculated limit of 118.8 dB μ V/m assumes free space conditions. This device was measured on a typical test site (OATS) with a reference ground plane as described in ANSI C63.4. This maximum value was obtained with the EUT set up at a height of 80cm. Placing the EUT at a height of 100cm reduces the maximum amplitude measured by about 3-4dB.

Test Conditions:

Power output measurements were performed on an Open Area Test Site at a distance of 3meter. The antenna for this device is integral.

SA Settings:

RBW $\geq$ Emission BW (or increased until no more than 0.5 dB change in power), VBW $\geq 3 \times$ RBW

Span = zero, centered on channel center, Sweep: fast enough to resolve transmit pulse

Detection: Peak

APPLICANT: ASCALADE TECHNOLOGIES INC.

FCC ID: PBWB187R26H

MODEL #: VOIP3211S/17

REPORT #: V:\A\Ascalade\321AUT6\321AUT6REVTestReport.doc

Results:

3.1.1 BASE:

BASE	Ascalade Technologies Inc.					
327AUT6	3/3/2006					
Tuned Frequency MHz	Emission Frequency MHz	Meter Reading dBuV	Ant. Polarity	Coax Loss dB	Correction Factor dB	Field Strength dBuV/m
1,921.5	1,921.54	83.0	V	2.84	31.04	116.88
1,921.5	1,921.54	84.1	H	2.84	31.04	117.98
1,925.0	1,924.99	83.6	V	2.84	31.06	117.50
1,925.0	1,924.99	84.1	H	2.84	31.06	118.00
1,928.5	1,928.45	83.0	V	2.84	31.08	116.92
1,928.5	1,928.45	84.2	H	2.84	31.08	118.12

APPLICANT: ASCALADE TECHNOLOGIES INC.
FCC ID: PBWB187R26H
MODEL #: VOIP3211S/17
REPORT #: V:\A\Ascalade\321AUT6\321AUT6REVTestReport.doc

3.1.2 HANDSET:

HANDSET	Ascalade Technologies Inc.					
321AUT6	3/3/2006					
Tuned Frequency MHz	Emission Frequency MHz	Meter Reading dBuV	Ant. Polarity	Coax Loss dB	Correction Factor dB	Field Strength dBuV/m
1,921.5	1,921.50	82.5	H	2.84	30.73	116.07
1,921.5	1,921.50	83.8	V	2.84	30.73	117.37
1,924.9	1,924.90	80.5	H	2.84	30.75	114.09
1,924.9	1,924.90	84.4	V	2.84	30.76	118.00
1,928.4	1,928.40	82.1	H	2.84	30.77	115.71
1,928.4	1,928.40	84.4	V	2.84	30.77	118.01

APPLICANT: ASCALADE TECHNOLOGIES INC.
FCC ID: PBWB187R26H
MODEL #: VOIP3211S/17
REPORT #: V:\A\Ascalade\321AUT6\321AUT6REVTestReport.doc

TRANSMITTER SPURIOUS EMISSIONS

Clause: 15.319 (g) and 15.323(d)

Test procedure: ANSI C63.17 section 6.1.1

Technical requirements/Limits:

15.319(g) Notwithstanding other technical requirements specified in this subpart, attenuation of emissions below the general emission limits in Section 15.209 is not required.

15.323(d) Emissions outside the sub-band shall be attenuated below a reference power of 112 milliwatts as follows: 30 dB between the sub-band and 1.25 MHz above or below the sub-band; 50 dB between 1.25 and 2.5 MHz above or below the sub-band; and 60 dB at 2.5 MHz or greater above or below the subband. Compliance with the emission limits is based on the use of measurement instrumentation employing peak detector function with an instrument resolution bandwidth approximately equal to 1.0 percent of the emission bandwidth of the device under measurement.

Test Conditions:

Lowest and Highest channel only. Radiated on an Open Area Test Site at a distance of 3meter.

Results:

3.1.3 BASE TRANSMITTER SPURIOUS EMISSIONS :

BASE	Ascalade Technologies Inc.						
327AUT6	3/3/2006						
Tuned Frequency MHz	Emission Frequency MHz	Meter Reading dBuV	Ant. Polarity	Coax & Filter Loss dB	Correction Factor dB/m	Field Strength dBuV/m	dBc
1,921.5	3,843.07	7.3	H	4.36	33.71	45.37	73.61
1,921.5	3,843.07	8.9	V	4.36	33.71	46.97	72.01
1,921.5	5,764.61	3.1	V	5.23	35.33	43.66	75.32
1,921.5	5,764.61	4.5	H	5.23	35.33	45.06	73.92
1,925.0	3,849.98	7.0	H	4.36	33.72	45.08	72.91
1,925.0	3,849.98	9.7	V	4.36	33.72	47.78	70.22
1,925.0	5,774.98	1.7	V	5.23	35.35	42.28	75.72
1,925.0	5,774.98	2.3	H	5.23	35.35	42.88	75.12
1,928.5	3,856.89	7.3	H	4.37	33.73	45.40	72.92
1,928.5	3,856.89	8.8	V	4.37	33.73	46.90	71.42
1,928.5	5,785.34	1.8	V	5.24	35.37	42.41	75.91
1,928.5	5,785.34	2.2	H	5.24	35.37	42.81	75.51

- The limit for all harmonic emissions are = 60dBc.

APPLICANT: ASCALADE TECHNOLOGIES INC.

FCC ID: PBWB187R26H

MODEL #: VOIP3211S/17

REPORT #: V:\A\Ascalade\321AUT6\321AUT6REVTestReport.doc

3.1.4 HANDSET TRANSMITTER SPURIOUS EMISSIONS :

HANDSET	Ascalade Technologies Inc.						
321AUT6	3/3/20906						
Tuned Frequency MHz	Emission Frequency MHz	Meter Reading dBuV	Ant. Polarity	Coax & Filter Loss dB	Correction Factor dB/m	Field Strength dBuV/m	dBc
1,921.5	3,843.00	2.9	H	4.36	33.57	40.83	76.54
1,921.5	3,843.00	4.1	V	4.36	33.57	42.03	75.34
1,921.5	5,764.50	1.5	H	5.23	35.42	42.15	75.22
1,921.5	5,764.50	1.7	V	5.23	35.42	42.35	75.02
1,924.9	3,849.90	3.5	H	4.36	33.58	41.44	75.75
1,924.9	3,849.90	4.3	V	4.36	33.58	42.24	74.95
1,924.9	5,774.90	1.0	H	5.23	35.43	41.66	75.53
1,924.9	5,774.90	1.1	V	5.23	35.43	41.76	75.43
1,928.4	3,856.90	5.8	V	4.37	33.59	43.76	74.25
1,928.4	3,856.90	6.0	H	4.37	33.59	43.96	74.05
1,928.4	5,785.40	1.0	V	5.24	35.44	41.68	76.33
1,928.4	5,785.40	1.4	H	5.24	35.44	42.08	75.93

- The limit for all harmonic emissions are = 60dBc.

APPLICANT: ASCALADE TECHNOLOGIES INC.
FCC ID: PBWB187R26H
MODEL #: VOIP3211S/17
REPORT #: V:\A\Ascalade\321AUT6\321AUT6REVTestReport.doc

3.2 GENERAL RADIATED SPURIOUS EMISSIONS

3.2.1 RADIATED SPURIOUS EMISSIONS

Clause: 15.109, 15.33, and 15.31

Test procedure: ANSI C63.4 - 2003

Technical requirements/Limits:

Emission Frequency (MHz)	Field Strength		At Distance (m)	Detector Type
	(µV/m)	(dBµV/m)		
0.009 – 0.490	2400/f (kHz)	67.6 / kHz	300	AV (9-90 kHz, 110-490 kHz) QP (others)
0.490 – 1.705	24000/f (kHz)	87.6 / kHz	30	QP
1.705 – 30.0	30	29.5	30	QP
30 – 88	100	40	3	QP
88 – 216	150	43.5	3	QP
216 – 960	200	46	3	QP
> 960	500	54	3	AV (> 1GHz)

Test Conditions:

Lowest and Highest channel only. Radiated on an Open Area Test Site at a distance of 3meter.

PK: RBW ≥ 100 kHz for f < 1 GHz, 1 MHz for f ≥ 1 GHz, VBW ≥ RBW

Avg: RBW = 1 MHz for f ≥ 1 GHz, VBW = 10Hz, Linear average. If the emission is pulsed, the device was modified for continuous operations, and the average level was calculated according to part 15.35(c)

APPLICANT: ASCALADE TECHNOLOGIES INC.

FCC ID: PBWB187R26H

MODEL #: VOIP3211S/17

REPORT #: V:\A\Ascalade\321AUT6\321AUT6REVTestReport.doc

Results:

3.2.2 BASE IN STAND-BY MODE:

Emission Frequency MHz	Meter Reading dBuV	Ant Pol	Coax Loss dB	Correction Factor dB	Field Strength dBuV/m	Margin dB
30.70	14.6	H	0.40	13.56	28.56	11.44
31.52	14.9	V	0.41	11.82	27.13	12.87
33.78	22.9	V	0.42	10.96	34.28	5.72
77.22	5.8	H	0.59	6.82	13.21	26.79
85.80	10.7	V	0.61	8.07	19.38	20.62
95.33	7.4	V	0.64	10.76	18.80	24.70
119.98	7.3	H	0.67	13.61	21.58	21.92
167.99	7.4	H	0.77	14.86	23.03	20.47
228.02	7.0	H	0.96	11.50	19.46	26.54
228.04	7.7	V	0.96	11.20	19.86	26.14
365.04	6.2	H	1.17	15.10	22.47	23.53
381.34	6.4	H	1.18	15.45	23.03	22.97
419.58	9.2	V	1.22	16.00	26.42	19.58
507.24	8.8	V	1.32	18.33	28.45	17.55
602.29	10.7	H	1.60	19.19	31.49	14.51

3.2.3 HANDSET IN STAND-BY MODE:

Emission Frequency MHz	Meter Reading dBuV	Ant Pol	Coax Loss dB	Correction Factor dB	Field Strength dBuV/m	Margin dB
80.50	5.1	H	0.60	6.66	12.36	27.64
80.50	9.6	V	0.60	6.81	17.01	22.99
85.70	7.4	H	0.61	7.34	15.35	24.65
85.70	11.4	V	0.61	8.04	20.05	19.95
95.30	6.0	H	0.64	9.53	16.17	27.33
95.30	8.8	V	0.64	10.75	20.19	23.31
560.00	3.8	H	1.48	18.80	24.08	21.92
560.00	8.4	V	1.48	18.10	27.98	18.02
911.60	16.3	H	1.97	23.38	41.65	4.35
911.60	17.7	V	1.97	22.60	42.27	3.73

APPLICANT: ASCALADE TECHNOLOGIES INC.
FCC ID: PBWB187R26H
MODEL #: VOIP3211S/17
REPORT #: V:\A\Ascalade\321AUT6\321AUT6REVTestReport.doc

3.2.4 AC POWER LINES CONDUCTED SPURIOUS EMISSIONS:

Clause: 15.315, 15.207, 15.107, 15.31

Test procedure: ANSI C63.4 - 2003

Technical requirements/Limits:

FCC:

Emission Frequency (MHz)	FCC Conducted Limit (dBμV)	
	Quasi-peak (QP)	Average (AV)
0.15 - 0.5	66 to 56 *	56 to 46 *
0.5 - 5	56	46
5 - 30	60	50

* Decreases with the logarithm of the frequency.

IC: 250 μV (48 dBμV) within 0.45-30 MHz using CISPR method of measurement

Test Conditions:

PK and QP(detector): RBW = 10kHz VBW>RBW

Avg: RBW = 10kHz VBW = 10Hz

APPLICANT: ASCALADE TECHNOLOGIES INC.

FCC ID: PBWB187R26H

MODEL #: VOIP3211S/17


REPORT #: V:\A\Ascalade\321AUT6\321AUT6REVTestReport.doc

Results:

Base is connected to power source through adapter and is in test mode
LINE 1:

NOTES:
ASCALADE TECHNOLOGIES INC. - FCC ID: PWB B187R26
THE BASE UNIT IN TEST MODE - LINE 1

FCC 15.107 Mask Class B




APPLICANT: ASCALADE TECHNOLOGIES INC.
FCC ID: PBWB187R26H
MODEL #: VOIP3211S/17
REPORT #: V:\A\Ascalade\321AUT6\321AUT6REVTestReport.doc

LINE 2:

NOTES:
ASCALADE TECHNOLOGIES INC. - FCC ID: PWB B187R26
THE BASE UNIT IN TEST MODE - LINE 2

FCC 15.107 Mask Class B




APPLICANT: ASCALADE TECHNOLOGIES INC.
FCC ID: PBWB187R26H
MODEL #: VOIP3211S/17
REPORT #: V:\A\Ascalade\321AUT6\321AUT6REVTestReport.doc

Base is connected to power source and is in standby-mode.
LINE 1:

NOTES:
ASCALADE TECHNOLOGIES INC. - FCC ID: PWB B187R26
THE BASE UNIT IN STANDBY MODE - LINE 1

FCC 15.107 Mask Class B




APPLICANT: ASCALADE TECHNOLOGIES INC.
FCC ID: PBWB187R26H
MODEL #: VOIP3211S/17
REPORT #: V:\A\Ascalade\321AUT6\321AUT6REVTestReport.doc

LINE 2:

NOTES:
ASCALADE TECHNOLOGIES INC. - FCC ID: PWB B187R26
THE BASE UNIT IN STANDBY MODE - LINE 2

FCC 15.107 Mask Class B



APPLICANT: ASCALADE TECHNOLOGIES INC.
FCC ID: PBWB187R26H
MODEL #: VOIP3211S/17
REPORT #: V:\A\Ascalade\321AUT6\321AUT6REVTestReport.doc

4 TEST EQUIPMENT AND ANCILLARIES USED FOR TESTS

Device	Manufacturer	Model	Serial Number	Cal/Char Date	Due Date
3/10-Meter OATS	TEI	N/A	N/A	Listed 3/27/04	3/26/07
3-Meter OATS	TEI	N/A	N/A	Listed 1/11/06	1/10/09
Biconnical Antenna	Eaton	94455-1	1057	CAL 12/12/05	12/12/07
Biconnical Antenna	Eaton	94455-1	1096	CAL 8/17/04	8/17/06
Biconnical Antenna	Electro-Metrics	BIA-25	1171	CAL 4/29/05	4/29/07
Blue Tower Quasi-Peak Adapter	HP	85650A	2811A01279	CAL 4/13/05	4/13/07
Blue Tower RF Preselector	HP	85685A	2926A00983	CAL 4/13/05	4/13/07
Blue Tower Spectrum Analyzer	HP	8568B	2928A04729 2848A18049	CAL 4/13/05	4/13/07
Double-Ridged Horn Antenna	Electro-Metrics	RGA-180	2319	CAL 12/29/04	12/29/06
LISN	Electro-Metrics	ANS-25/2	2604	CAL 8/27/04	8/27/06
LISN	Electro-Metrics	EM-7820	2682	CAL 4/28/05	4/28/07
Log-Periodic Antenna	Eaton	96005	1243	CAL 12/14/05	12/14/07

APPLICANT: ASCALADE TECHNOLOGIES INC.
FCC ID: PBWB187R26H
MODEL #: VOIP3211S/17
REPORT #: V:\A\Ascalade\321AUT6\321AUT6REVTestReport.doc

5 TEST SETUP PHOTOGRAPHS

RADIATED TEST SET UP (BASE ON TABLE):




APPLICANT: ASCALADE TECHNOLOGIES INC.

FCC ID: PBWB187R26H

MODEL #: VOIP3211S/17

REPORT #: V:\A\Ascalade\321AUT6\321AUT6REVTestReport.doc

RADIATED TEST SET UP (HANDSET):



APPLICANT: ASCALADE TECHNOLOGIES INC.

FCC ID: PBWB187R26H

MODEL #: VOIP3211S/17

REPORT #: V:\A\Ascalade\321AUT6\321AUT6REVTestReport.doc

POWERLINE CONDUTED TEST SET UP:



APPLICANT: ASCALADE TECHNOLOGIES INC.

FCC ID: PBWB187R26H

MODEL #: VOIP3211S/17

REPORT #: V:\A\Ascalade\321AUT6\321AUT6REVTestReport.doc

6 EUT EXTERNAL PHOTOGRAPHS

The photos are provided in a separate exhibit

7 EUT INTERNAL PHOTOGRAPHS

The photos are provided in a separate exhibit

8 LABEL PHOTOGRAPHS

The label sample and location are provided in a separate exhibit

APPLICANT: ASCALADE TECHNOLOGIES INC.

FCC ID: PBWB187R26H

MODEL #: VOIP3211S/17

REPORT #: V:\A\Ascalade\321AUT6\321AUT6REVTestReport.doc