

# USR015476, USR805476 & USR815476 WIRELESS ADSL2+ STARTER KIT

BROADBAND  
WIRELESS NETWORKING

The USRobotics Wireless ADSL2+ Starter Kit includes everything you need to bring the convenience of wireless broadband networking to your home or small business. The Wireless ADSL2+ Router includes an ADSL modem, firewall, and 802.11g wireless access point, allowing it to be connected directly to your ADSL line. The 802.11g Wireless USB Adapter can be plugged into a laptop or desktop PC for incredibly flexible wireless broadband connectivity. Now you can easily, and safely, surf without wires!

## USRobotics®

### Everything you need to securely share your ADSL Internet connection



#### *Five Products in One*

Includes integrated ADSL2+ modem, broadband router, firewall and 802.11g wireless access point and 802.11g USB adapter

#### *Great Wireless Compatibility*

- Surf without wires!
- Complete compatibility with standard 802.11b (11 Mbps) & 802.11g (54 Mbps)

#### *Solid Security*

Built-in security protects your network against hackers

- Stateful Packet Inspection firewall
- Parental Control – Control PC access to the Internet by time of day and day of week
- For business users, VPN pass-through support for PPTP, IPsec, and L2TP
- Encryption - WEP 64/128 bit, WPA
- Mac Address Authentication, Disable Broadcast SSID

#### *Easy to Install and Use*


- Simple 1-2-3 installation will have you up and sharing your Internet connection in minutes

#### *Universal Connectivity*

- Ethernet port for connecting wired devices directly, or add additional hubs or switches for up to 253 connections (including wireless)


#### *Flexibility and Portability*

- Wireless USB adapter works with both USB 2.0 and USB 1.1 ports, on laptop or desktop PCs





Model 9111  
Wireless ADSL2+ Router



Model 5423  
Wireless USB  
Adapter



OR



## USR015476, USR805476 & USR815476 WIRELESS ADSL2+ STARTER KIT



### SPECIFICATION AND STANDARDS

#### Wireless ADSL2+ Router (Model 9111) ADSL

- Supports ADSL2/ADSL2+
- S=1/2 for up to 12 Mbps
- Supports full-rate G.DMT (ITU-T G.992.1) and T1.412 Issue 2 ADSL: up to 8 Mbps downstream and up to 1 Mbps upstream†
- Supports G.lite (ITU-T G.992.2) ADSL: up to 1.5 Mbps downstream and up to 512 Kbps upstream†
- Supports DSL handshaking (ITU-T G.994.1)
- RFC 2516 PPP over Ethernet (Client)
- RFC 2364 PPP over ATM
- RFC 2684 (formerly 1483) Multi-protocol over ATM (Bridged and Routed)
- Annex A
- ATM Forum UNI 3.0, 3.1
- ITU-T Q.2931, Q.2971 signaling, ITU-T I.363.5 ATM AAL5
- Service Classes for Traffic Shaping: CBR, UBR
- Virtual Circuits 4 PVC
- Encapsulation LLC/SNAP & VC Mux

#### Wireless

- Complies with IEEE 802.11g 54 Mbps and 802.11b 11 Mbps wireless standards
- Operating Channels: 13 (Europe - ETSI)

#### Networking

- Auto MDI/MDIX support on LAN port
- Static and dynamic IP addressing
- Network Address Translation (NAT), Dynamic NAT
- DHCP server (LAN) and client (WAN)
- PPPoE Client Support
- Supports up to 253 clients (with additional hubs or switches)
- Virtual Server, Application Mapping

#### Security

- Integrated firewall protection for security
- VPN pass-through support for PPTP, IPsec, and L2TP
- DMZ support
- WiFi Protected Access (WPA)-PSK (including TKIP)
- WEP, AES
- Encryption - WEP 64/128 bit
- Denial of Service
- Access Control List (Time of Day & IP Address)
- Mac Address Authentication, Disable Broadcast SSID

#### Physical

- Visual diagnostic LEDs: Power, WAN, LAN, WLAN, ADSL
- One RJ-11 ADSL port
- One RJ-45, 10/100 Mbps Ethernet LAN port

#### Dimensions

- 6.13 x 5 x 1.12 inches (15.6 x 12.7 x 2.84 cm)

#### Wireless USB Adapter (Model 5423)

##### General

- Complies with IEEE 802.11g 54 Mbps and 802.11b 11 Mbps wireless standards
- Operating Channels: 13 (Europe - ETSI)
- USB 2.0 (backward compatible with USB 1.1)

##### Security

- Encryption - WEP 64/128 bit, WPA-PSK

##### Physical

- Low profile stick format
- Visual diagnostic LED

##### Dimensions

- 3.25 x 1.06 x .47 inches (8.26 x 2.7 x 1.2 cm)

#### Wireless ADSL2+ Starter Kit

##### Regulatory

- CE Approved

##### Package Dimensions

- 13.26 x 8.06 x 3.21 inches (33.68 x 20.47 x 9.25 cm)
- Weight: 2.6 lb (1.18 Kg)

##### Environmental

- Operating/Non-operating Temperature: 0~50° C/-20~70° C
- Operating/Non-operating Humidity: 20%~80%/5%~95% non-condensing

##### Language Support

- **Retail box:** English, French, German, Spanish, Italian, Dutch, Turkish, Arabic
- **Installation guide:** English, French, German, Spanish, Italian, Dutch, Turkish
- **CD ROM User Guide:** English, French, German, Spanish, Italian, Dutch, Portuguese, Arabic, Czech, Polish, Russian, Hungarian, Turkish, Swedish

##### Package Contents

- Wireless ADSL2+ Router
- Wireless USB Adapter
- Ethernet cable
- Phone cable
- Micro-filter (USR815476 only)
- Power adapter
- Quick Installation Guide
- Installation CD-ROM with User Manual

##### Minimum System Requirements

- **Wired** - Connect any device that supports 10/100 Mbps Ethernet and RJ-45 connector
- **Wireless** - Works with any 802.11g/802.11b wireless device
- **USB Adapter** - Any desktop or laptop with available USB port and Windows 98SE/Me/2000/XP (Service Pack 1 & 2)
- **Installation** - Requires HTML 4.01 compliant browser

##### Warranty

- Two-year limited manufacturer warranty from date of purchase

†ADSL speeds depend on telephone company service offerings and distance from telco central office.