

MODEL 5635
56K* USB MINI FAXMODEM

ANALOG

The USRobotics 56K* USB Mini Faxmodem infuses quality and reliability with USB convenience and the enhanced performance of V.92 technology. Quick Connect reduces your connection time to get you online quicker, and V.PCM Upstream provides 50% greater upload speeds — perfect for sending e-mail messages with large attachments. Internet Call Notification lets you screen incoming voice calls while online, so you won't miss the important ones, and Modem on Hold allows you to answer them without losing your internet connection — no second phone line is needed!



USRobotics®

Simple Plug and Play installation

USB convenience and ease of use

- Simple USB Plug and Play installation
- Hot-swappable (installs/uninstalls automatically)
- Bus-powered so it doesn't require an external power supply

Advanced features and functionality

- Send and receive faxes through your computer while running other applications
- Supports group faxing and timed faxing
- Permanently store preferred modem default settings

Get the speed you need

- Quick Connect reduces the time it takes to establish your dial-up Internet connection.
- Need to send digital pictures or a large presentation? V.92 lets you send attachments up to 50% faster!

Powerful Management Tools

- USRobotics Internet Call Notification (ICN) lets you screen incoming calls so you can take the important ones†
- Modem on Hold lets you take calls while online without dropping your Internet connection — there's no need for a second phone line

Software Upgradable

- Firmware upgradability and downloadable software ensure that this modem will continue to meet your changing needs

Advanced Line Probing Technology

- This modem finds the most efficient path for each connection, assuring the best possible speeds, resulting in faster downloads and fewer dropped calls





Model 5635 USB Modem



PC with USB Port

MODEL 5635 56K* USB MINI FAXMODEM



SPECIFICATIONS & STANDARDS

GENERAL

- Data: V.92, V.90, V.34, V.32bis, V.32, V.22bis, V.22, V.23, and V.21
- Data Error Control/Compression: V.42/V42bis and MNP2-4/5
- Fax: EIA 578 (Class 1) with V.17, V.29, V.27ter, Group 3
- DTE interface: USB Version 1.1
- USB powered, consumption: 100 mA

PHYSICAL

- 2 LEDs: Power, Data
- Phone line interface: One RJ-11 socket
- Caller ID support (requires service from your local phone company; Caller ID may not be supported in some countries)

ENVIRONMENTAL

- **Temperature:** Operating Temperature conditions: 0 to 50 degrees C, Non-Operating Temperature conditions: -20 to 70 degrees C
- **Humidity:** Operating Humidity conditions: 20% to 80% non-condensing, Non-Operating Humidity conditions: 5% to 95% non-condensing

REGULATORY

- CE approved (Class B)
- FCC approved
- IC approved
- UL/CUL listed

PACKAGE DIMENSIONS/WEIGHT

- 7.64 x 5.83 x 1.38 in (19.4 x 14.8 x 3.5 cm)
- 0.69 lb (0.31 kg)

PRODUCT DIMENSIONS

- 3.75 x 3 x 1 in (9.52 x 7.62 x 2.54 cm)
- 0.2 lb (0.09 kg)

MINIMUM SYSTEM REQUIREMENTS

- Windows 2000/XP
- Intel Pentium III 600 MHz or equivalent, 128 MB RAM, 5 MB hard drive space
- USB port
- 2x or better CD-ROM drive
- Analogue phone line

PACKAGE CONTENTS

- USRobotics 56K* USB Mini Faxmodem
- USB cable
- Phone cord
- Quick Installation Guide
- Installation Essentials CD-ROM, including user's guide, data/fax software, and Internet Call Notification

WARRANTY

- 2-year limited manufacturer warranty from date of purchase

* Capable of receiving at up to 56 Kbps and sending at up to 48 Kbps (or 31.2 Kbps with V.90 server). Due to FCC regulations on power output, receiving speeds are limited to 53.3 Kbps. Actual speeds may vary. V.92 and V.90 features require compatible phone service and support from your Internet Service Provider (ISP). USRobotics modems featuring V.92 enhancements are backward compatible and will negotiate the highest possible speed when connecting to an ISP.

† Call Waiting service required for using Internet Call Notification (ICN) and Modem on Hold. Call Waiting/Caller ID service required for utilizing Caller ID feature of ICN.

For connection to the Public Switched Telephone Network (PSTN)

USRobotics®

IC Approved
Approuvé par IC

